

PRODUCTS - SOLUTIONS - RESOURCE

PRODUCT OVERVIEW:

The Activation Sub is a high performance built ball activated blanking device which allows for hydraulic activation of tools in the “ZONE SEEKER™” multi-stage stimulation system.

Once the Zone Seeker™ system has reached its target depth the tools are ready to be set in place. A 1” ball is dropped from surface and circulated down to the Activation Sub. Once the ball has seated, surface pressure is increased and the tool is activated. At this point the entire system is closed to the open hole and will remain closed until the delta port has been activated.

The Activation Sub is rated at full 10,000 psi differential pressure. Standard configuration are P-110 equivalent. Alternate materials and configurations are available for severe environments and higher differential pressure ratings. A full line of accessory equipment is available providing a complete open hole multi-stage stimulation system.

FEATURES:

- Short and slim design ensures liner flexibility and trouble free deployment in various well profiles.
- Compact design provides ease of handling, eliminates the need for handling joints, reduces leak paths and significantly increases rig floor safety.
- Reliable field proven ball activation system.
- Designed for open hole multi-stage stimulation applications.
- Composite phenolic activation balls combine high strength with low density.
- Available in corrosion resistant alloys for hostile environments.
- Standard and premium thread connections available.
- 10,000 psi differential pressure rating as standard.

